


REWARDING BRIGHTNESS


 With integrated GA-016
+ PSU adapter.

Available colors




Trackspots

Linea AS 3F

Specifications

Colour(s)	Matt white RAL9016 (XX=MW) / Black RAL 9005 (XX=BL) / Grey RAL 9006 (XX=GR)
Beam angle (FWHM)	18° / 37° / 60°
UGR (4H8H 70/50/20)	<19 (18° + 37°)
Fixture material	Diecast aluminium
Environment	Indoor
IK rate	IK02
Operating temperature (Ta)	-20°C / +45°C
Safety marks	EN60598 / EN62031 / EN 62471
EMC compliance	EN55015
Warranty	7 Years


 This luminaire contains
built-in LED lamps

 The lamps cannot be changed in
the luminaire.


874/2012



IP20

Item specifications

Description	Item code	Type	Inrush current	B-16A Fuse	Energy class	Safety class	Weight	Dimensions single carton	Quantity per carton
Linea AS 3400 Lm 4000K CRI80	170403XXYYE2	No dim	5A 50µS	50 stuks	A+	I	1355 gr	275x210x130 mm	8 pcs
Linea AS 3000 Lm 3000K CRI80	170403XXYYE2	No dim	5A 50µS	50 stuks	A+	I	1355 gr	275x210x130 mm	8 pcs
Linea AS 2500 Lm 3000K CRI96	170403XXYYE2	No dim	5A 50µS	50 stuks	A+	I	1355 gr	275x210x130 mm	8 pcs

Lumen settings

Linea AS 4000 K CRI 80

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
On request	350	13,0	1650	127	0.91	82	134.000 hrs	82.000 hrs	37.000 hrs	12.9	13.9	18.3
On request	500	17,6	2200	125	0.92	82	134.000 hrs	82.000 hrs	37.000 hrs	13.9	14.9	19.3
On request	700	26,5	3150	119	0.93	82	134.000 hrs	82.000 hrs	37.000 hrs	15.1	16.2	20.6
170403XXYYE2	800	31,7	3400	107	0.95	82	131.000 hrs	80.000 hrs	35.000 hrs	15.4	16.4	20.8

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (DD), 37° (DE), 60° (DF)

Linea AS 3000 K CRI 80

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
On request	350	13,0	1500	115	0.91	82	134.000 hrs	82.000 hrs	37.000 hrs	12.5	13.6	18.0
On request	500	17,6	2000	114	0.92	82	134.000 hrs	82.000 hrs	37.000 hrs	13.5	14.6	19.0
On request	700	26,5	2700	102	0.93	82	134.000 hrs	82.000 hrs	37.000 hrs	14.6	15.6	20.0
170403XXYYE2	800	31,7	3000	95	0.95	82	131.000 hrs	80.000 hrs	35.000 hrs	14.9	16.0	20.4

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (DA), 37° (DB), 60° (DC)


Linea AS 3000 K CRI 96

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
On request	350	13,0	1100	85	0.91	96	134.000 hrs	82.000 hrs	37.000 hrs	11.4	12.5	16.9
On request	500	17,6	1450	82	0.92	96	134.000 hrs	82.000 hrs	37.000 hrs	12.4	13.5	17.9
On request	700	26,5	2150	81	0.93	96	134.000 hrs	82.000 hrs	37.000 hrs	13.8	14.8	19.2
170403XXYYE2	800	31,7	2500	79	0.95	96	131.000 hrs	80.000 hrs	35.000 hrs	14.3	15.3	19.8

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (DG), 37° (DH), 60° (DJ)

Dimensions



Extra option

LEDs from the LUXEON Stylist Series
Specially developed for shops specialised in fashion or fresh food, and for restaurants. Ask our sales department about the possibilities.

